

Big Dot Indoor LED Display

The Big Dot indoor LED display delivers message clarity from up to 200 feet away, allowing you to visually connect with your employees or customers better than any poster or banner.



Pixel Size (Diameter):	0.35" (.89 cm)
Pixel (LED) Color:	8 bright colors and 3 rainbow effects.
Center-to-Center Pixel Spacing (Pitch):	0.57" (10.1 cm)
Character Size:	4.0" tall
Character Array:	5 x 7 matrix
Character Set:	Block (sans serif), decorative (serif), upper/lower case, slim/wide
Memory Retention:	2 weeks minimum
Message Capacity:	80 different messages can be stored and displayed
Message Operating Modes:	<ul style="list-style-type: none"> • 26 modes, including Automode™, Hold, Interlock, Roll (6 directions), Rotate, Sparkle-on, Twinkle, Spray-on, Slide across, Switch, Wipe (6 directions), Starburst, Flash, Snow, Scroll, and Condensed Rotate. • Continuous message entry with automatic centering in any mode • User programmable logos and graphics • Five hold speeds
Built in Animations:	Cherry Bomb Exploding, Don't Drink and Drive, Fireworks, Slot Machine, No Smoking, Running Animal, Moving Auto, Welcome (in script) and Thank You (in script)
Real-Time Clock:	Date and time, 12 or 24 hour format, maintains accurate time without power for up to 14 days.
Serial Computer Interface:	RS232, RS485
Power:	120 VAC or 230 VAC optional
Power Cord Length:	10 ft. (3m)
Keyboard:	Handheld IR remote with 54 key layout
Case Material:	UV stabilized high temperature ABS
Limited Warranty:	One-year parts and labor, factory servicing. Indoor use only.
Agency Approvals:	<ul style="list-style-type: none"> • ETL conforms to EN60950/IEC950 standard • Complies with part 15 of the FCC rules
Operating Temperature:	32° to 120° F, 0° to 49° C
Humidity Range:	0% to 95% non-condensing
Mounting:	Hardware to accommodate ceiling or wall mounting

SPECIFICATIONS	WINDOW DISPLAY
Case Dimensions LxDxH:	49.0" x 4.25" x 6.25" 124.5 cm x 11.0 cm x 16.0 cm
Display Dimensions LxH:	45.6" x 4.0" 115.8 cm x 10.16 cm
Display Weight:	12.25 lbs. (5.6 kg.)
Display Array:	80 columns x 7 rows
Characters Displayed per line One-line	typical/maximum 13/27
Display Memory:	28,000 characters