

LED Window Display

Our eye-catching Alpha LED Window Display is an easy-to-program, indoor electronic message center that offers message impact day and night, from a distance of 15 to 200 feet.



Pixel Size (Diameter):	0.35" (.89 cm)
Pixel (LED) Color:	<ul style="list-style-type: none"> • Super-bright red (standard), visible even in sunlight • Also available in amber (optional)
Center-to-Center Pixel Spacing (Pitch):	0.57" (10.1 cm)
Character Size:	4.0" tall
Character Array:	5 x 7 matrix
Character Set:	Block (sans serif), decorative (serif), upper/lower case, slim/wide
Memory Retention:	2 weeks minimum
Message Capacity:	80 different messages can be stored and displayed
Message Operating Modes:	<ul style="list-style-type: none"> • 26 modes, including Automode™, Hold, Interlock, Roll (6 directions), Rotate, Sparkle-on, Twinkle, Spray-on, Slide across, Switch, Wipe (6 directions), Starburst, Flash, Snow, Scroll, and Condensed Rotate. • Continuous message entry with automatic centering in any mode • User programmable logos and graphics • Five hold speeds
Built in Animations:	Cherry Bomb Exploding, Don't Drink and Drive, Fireworks, Slot Machine, No Smoking, Running Animal, Moving Auto, Welcome (in script) and Thank You (in script)
Real-Time Clock:	Date and time, 12 or 24 hour format, maintains accurate time without power for up to 14 days.
Serial Computer Interface:	RS232, RS485
Power:	120 VAC or 230 VAC optional
Power Cord Length:	10 ft. (3m)
Keyboard:	Handheld IR remote
Case Material:	UV stabilized high temperature ABS
Limited Warranty:	One-year parts and labor, factory servicing. Indoor use only.
Agency Approvals:	<ul style="list-style-type: none"> • ETL conforms to EN60950/IEC950 standard • Complies with part 15 of the FCC rules
Operating Temperature:	32° to 120° F, 0° to 49° C
Humidity Range:	0% to 95% non-condensing
Mounting:	Hardware to accommodate ceiling or wall mounting

SPECIFICATIONS	WINDOW DISPLAY
Case Dimensions LxDxH:	49.0" x 4.25" x 6.25" 124.5 cm x 11.0 cm x 16.0 cm
Display Dimensions LxH:	45.6" x 4.0" 115.8 cm x 10.16 cm
Display Weight:	12.25 lbs. (5.6 kg.)
Display Array:	80 columns x 7 rows
Characters Displayed per line One-line	typical/maximum 13/27
Display Memory:	28,000 characters