

BetaBrite® Classic LED Sign

The BetaBrite® Classic LED electronic message display is an economical way to get your message out faster and more efficiently than banners, paper signs, or other temporary - and often costly - indoor signage.



Pixel Size (Diameter):	0.2" (0.51 cm)
Pixel (LED) Color:	Red, amber and green; able to create eight color combinations and three rainbow effects
Center-to-Center Pixel Spacing (Pitch):	0.3" (0.76 cm)
Character Size:	2.1" tall
Character Set:	Block (sans serif); decorative (serif); upper/lower case; slim/wide
Memory Retention:	One month typical
Message Capacity:	65 different messages can be stored and displayed
Message Operating Modes:	26 styles including Automode™, Hold, Interlock, Roll (6 directions), Rotate, Sparkle-on, Twinkle, Spray-on, Slide across, Switch, Wipe (6 directions), Starburst, Flash, Snow, Scroll, Condensed rotate.
Built in Animations:	Cherry-bomb exploding, don't drink and drive, fireworks, slot machine, no smoking, running animal, moving auto, welcome (in script), thank you (in script), new flash, trumpets, party balloons and fish.
Real-Time Clock:	Date and time, 12 or 24 hour format, maintains accurate time without power for up to 30 days typical.
Computer Interface:	Serial / RS232 Option: 25' PC-to Display cable for connection to optional BetaBrite Software.
Power:	7.5 VDC at 3.25A, 50/60 HZ
Power Cord Length:	10 ft. (3m)
Keyboard:	Handheld IR remote
Case Material:	Extruded aluminum
Limited Warranty:	One-year parts and labor, factory servicing
Agency Approvals:	<ul style="list-style-type: none"> • 120 VAC model: Listed to ANSI/UL 60950-1 (US) and CAN/CSA C22.2 No. 60950-1-03 (Canada) • 230 VAC models: Complies with EN60950: 1992 (Europe) and AS/NZS 3260-1993 (Australia/ New Zealand) • FCC Part 15 Class A • ETL and UL Marked (120 VAC model) - CE and S Marked (230 VAC model)
Operating Temperature:	32° to 120° F, 0° to 49° C
Humidity Range:	0% to 95% non-condensing
Mounting:	Hardware to accommodate ceiling or wall mounting

SPECIFICATIONS	BETABRITE® CLASSIC LED DISPLAY
Case Dimensions LxDxH:	25.8"L x 2.0"D x 3.8"H
Approximate Weight:	2.55 lbs. (1.16 kg.) without power supply and keyboard
Display Dimensions:	24.0"L x 2.1"H
Display Array:	80 columns x 7 rows
Display Memory:	30,000 characters